

ATF 3 semi synthetic

maxxpower premium ATF 3 semi synthetic

Product properties

maxxpower premium ATF 3 is an automatic transmission fluid that provides excellent cold flow behavior and oxidation properties plus good corrosion protection and foaming behavior. maxxpower premium ATF 3 has optimally balanced friction behavior and excellent wear protection.

Area of application

maxxpower premium ATF 3 is an automatic transmission fluid for use in servo steering systems, hydrodynamic converters and hydraulics in vehicles, trucks, buses and construction vehicles, for use where the manufacturer specifications state ATF Type Dexron III H is required.

Application

Specifications / Recommendations

Allison C-4
Allison TES, 389
DEXRON III H
DEXRON III G
Ford M2C138-CJ, M2C 166-H
Ford Mercon
MAN 339 Typ Z1 + V1, Z2 + V2
MB 236.1, 236.5, 236.6 + 236.7
Voith 55.6335 + 55.6336
Volvo 97340, 97341
ZF TE-ML 02F, 04D, 09,11A, 14A + 17C

Technical data

Colour: red
Odour: characteristic
Physical state: liquid
Pourpoint: -50 °C (ISO 3016)/ -58 °F (ISO 3016)
Flashpoint: 220 °C (DIN ISO 2592)/ 428 °F (DIN ISO 2592)
Lower explosion limit: 0,6 Vol.-%
Upper explosion limit: 6,5 Vol.-%
Density at 68 °F: 0,848 g/cm³ (DIN 51757)
Water resistant
Solvent content: 0,0 %
viscosity at 104°F (mm²/s): 40
viscosity at 212°F (mm²/s): 8,1
viscosity index: 182

Available size	Item no.	PU
1L	36900	12
5L	36901	3
20L	36902	1



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.